

# Cleveland Stainless Steel Reducers

- \* Housing, Covers & Motor Flange of Cast 316 Stainless Steel.
- \* Solid Output Shafts & Hollow Output Shaft Units of 303 Stainless Steel material.
- \* All Bearing Covers & Motor Flange connections O-ring sealed.
- \* All Fasteners are Stainless Steel solid cap screws & all Housings Plugs are Stainless Steel male types.
- \* Seals are Double Lip, Spring Loaded Viton. Output seals are encapsulated to prevent seal casing corrosion.
- \* Motor Flanges have two tapped holes for easy removal of motor.
- \* Every unit includes a Mounting Accessory Kit-Stainless Steel motor mounting bolts, Stainless Steel Breather Vent & O-ring to provide a positive seal between the motor and gearbox flange.
- \* All units supplied Factory Filled with ISO PAG 460 H1 Food Grade Synthetic Oil.



# ...the Answer for Food, Beverage & Tough Environmental Applications.

\* Designed for Frequent & Harsh Wash Down Conditions - Resists Contamination & Bacteria Growth.

\* Cleveland Gear Part Number Laser Etched onto Reducer.

\* Tapped Top Mounting Holes Available if Required (optional)

\* Matte Finish Aids in Thermal Dispersion.



<b>C.D. Sizes</b>	<b>Solid Output Shaft</b> (Single or Double)	<b>Hollow Output Shaft</b> (Symetrical w/ Stainless Steel Set Screws)
<b>17</b>	<b>S 1713</b>	<b>S 1714</b>
<b>20</b>	<b>S 2013</b>	<b>S 2014</b>
<b>20 G</b>	<b>S 2013 G</b>	<b>S 2014 G</b>
<b>26</b>	<b>S 2613</b>	<b>S 2614</b>
<b>26 G</b>	<b>S 2613 G</b>	<b>S 2614</b>

**Ratios Available:** 5.1, 7.5:1, 10:1, 15:1, 20:1, 25:1, 30:1, 40:1, 50:1, 60:1

**Motor Flanges:** Size 17 & 20 – 56C & 140TC / Size 26 – 56C, 140TC & 180TC

**Hollow Output Bores:** Size 17 – 5/8", 3/4" & 1.0"  
Size 20 – 1.0", 1 1/4" & 1 7/16"  
Size 26 – 1 3/16", 1 1/4" & 1 7/16"



Note: For Ratings and Dimensional Information, please see Cleveland Gear Catalog on "M" Series Modular Gearboxes (#410)